



NIB NTN 51101 THRUST BEARING 13x26x9 mm NEW

Bearing No. 51101

51101 Bearing 2D drawings and 3D CAD models

Size	12x26x9 mm
Bore Diameter	12 mm
Outer Diameter	26 mm
Width	9 mm
d	12 mm
D	26 mm
T	9 mm
d1	26 mm
r min.	0,3 mm
D1	13 mm
da min.	20 mm
Da max.	18 mm
ra max.	0,3 mm
Weight	0,023 Kg
Basic dynamic load rating (C)	10,3 kN
Basic static load rating (C0)	15,4 kN
(Grease) Lubrication Speed	6 400 r/min
Category	Thrust Ball Bearing
Inventory	6.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.03
EAN	4547359305821
Product Group	B00308
Rolling Element	Ball Bearing

Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row With Flat Seat
Long Description	12MM Bore 1; 13MM Bore 2; 26MM Outside Diameter; 9MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; ABEC 1 ISO P0 Precision
Inch - Metric	Metric
Category	Thrust Ball Bearings
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	51101
Weight / LBS	0.05071
Height	0.354 Inch 9 Millimeter
Bore 2	0.512 Inch 13 Millimeter
Outside Diameter	1.024 Inch 26 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Bore 1	0.472 Inch 12 Millimeter
bore diameter:	12 mm
dynamic load capacity:	10300 N
outside diameter:	26 mm
operating temperature range:	-40 to 120 ° C

overall width:	9 mm
maximum rpm:	9200 rpm
thrust bearing type:	Single-Direction
bearing material:	High Carbon Chrome Steel
outside diameter design:	Straight
cage material:	Resin
separable or banded:	Separable
fillet radius:	0.3 mm
precision rating:	ISO Class 0
series:	511
static load capacity:	15400 N
manufacturer product page:	Click here